LED Canpoy Light Ultra-thin Series











Attention before installation

- Cut off the power and make sure the wall can support the weight of the lamp before installation.
- Make sure the lamp is securely mounted.
- Do not cover the lamp with anything which will be harmful for heat dissipation.
- Installation by licensed electrician only.
- 5 year warranty against any manufacturing defects. 50,000 hrs L70 lifetime.
- Product failure caused by misuse, modification or power surges will not be covered under warranty.

Applications



 Parking structures, storage areas and low level security

Features

- Sealed die-casting profile for indoor applications
- Replacing 100-400W MH
- Lumen output from 3800-6000lm.
- Three 1/2" threaded conduit and one 3/4" conduit entry points
- Polycarbonate optical lens with heat resisting
- Multiple voltage input is available, support 347V and 480V input
- Motion sensor is available
- Ultra-thin design

Common Features

- Input Voltage:100-277 VAC
- Efficacy: ≥86LPW
- Color Rendering Index (CRI): ≥75
- 50,000 hour life
- THD < 4.75%
- Power Factor: 0.99
- Frequency: 50-60Hz
- IP65

ORDERING INFORMATION (Example=E2CP-45W-27V-5000K-D)

MODEL	POWER CONSUMPTION	VOLTAGE	CCT	FINISH	LUMEN	CRI
E2CP45W27V50KYY	45W	27V=100~277V	50K=5000K	B=Black	4000	75
E2CP70W27V50KYY	70W				6000	

Comment: • 347-480V power driver is only available for 45W led canopy

 $[\]bullet \ \ 277 V \ driver operates on 120-277 V \ (50/60 \ Hz), Specify 120 \ and \ 240-277 \ options \ only \ when \ ordering \ with \ Motion \ ordering \ with \ Motion \ ordering \ when \ ordering \ with \ Motion \ ordering \ when \ ordering \ when \ ordering \ with \ Motion \ ordering \ when \ ordering \ orderin \ ordering \ ordering \ ordering \ ordering \ ordering \ orderi$

Dimension









