

LED Vapor proof fixture

Model: E2-VL4240/4254

DLC 4.0



Dimension: 1270*165*105mm



PRODUCT DESCRIPTION:

This LED Vapor-proof fixture comes with 40 watt or 54 watt optional. Operating between 100 and 277 volts, this fixture features a 50 inches, one piece, non-corrosive, polycarbonate lens and body for long exterior life. Engineered to use less wattage while achieving about 130-140Lm/w, widely used at garages, stairwells, storage areas and other wet and harsh environments.

FEATURES:

- Durable body and lens
- Optional surface or suspended mounted
- Engineered low drive rates for cooler operating temperatures
- Milky white and clear Polycarbonate lens with inside ribbing made the fixture impact resistance and UV stabilized
- UL listed for wet location, IP65 rated
- 5-Year Manufacturer Warranty
- Lumen output greater than 130LPW
- 50,000 Hours L70 Lifespan
- cUL, UL Comply with UL1993/UL8750

Option:

1. 200-480VAC available for special order.
2. Motion sensor is available
3. Surface or suspended mount

APPLICATION:

- Office, garage, Commercial and Industrial Buildings

TESTED DATA:

- Light Output: 5000LM /7500LM
- Wattage: 40W/ 54W
- Efficacy: >130 LPW
- Power Factor: >0.90
- CCT: 4000K, 5000K
- CRI: >83
- THD: <20%
- Frequency: 50-60Hz
- Input Voltage: AC100-277V
- Working Environment: -24°F-122°F
- Beam Angle: 120°
- Mercury Content: No Hg
- Lens: Polycarbonate lens

Ordering Information

Example: E2-VL4254UV50K

FAMILY		SIZE		WATT		VOLTAGE		CCT		LIGHTING CONTROL		OPTICS	
E2-VL	LED Vapor proof fixture	42	4FT	54	54W	UV HV	120-277VAC 200-480VAC	50K	4000K	(blank) 10D	Static 0-10V Dim	CL FR	Clear Frost
				40	40W			40K	5000K				
								55K					
								57K					