

PROJECT NAME:	CATALOG NUMBER:	
NOTES:	EIVTLIDE COLIEDLII E	

Page: 1 of 2

LED Slim (1.97") TROFFER Fixtures E2-TRS22/24 Series

RoHS

White Power coat finish



PHYSICAL SPECIFICATION: 2 X 4

Length: 47.717"(1212mm) Width: 23.74" (603mm) Height: 1.97" (50mm) Weight: 17 lbs



PHYSICAL SPECIFICATION: 2 X 2

Length: 23.74 (603mm) 23.74" (603mm) Width: 1.97" (50mm) Height: Weight: 10 lbs

PRODUCT DESCRIPTION:

The E2-TRS22/24 Slim LED troffer fixture is a design based on the idea of green energy . It saves over 50% energy compared with the fluorescent troffer. The WL-TRS22/24 accepts 100-277VAC, and have a high lumen efficiency up to 125-130Lm/W. Our welldistributed uniform LED placement, soft light, high stability, long life, elegant and special external design, this Luminaries is regarded as the leading of greening Lighting for commercial and industrial uses.

FEATURES:

- 50,000 Hours L70 Lifespan
- . ETL and DLC® Premium 4
- Size 2×4 available watt 24W/36W/42W/50W
- Size 2×2 available watt 24W/36W
- CCT Available: 3500K, 4000K, 5000K
- 125Lm+/W
- · Optional:microwave sensor
- Internal Driver
- Standard PC diffuser
- 0-10V Dimming optional
- Emergency battery back-up 90 mins

APPLICATION:

- · Residential Buildings, Home, Office, Meeting
- School, Library, Factory, Warehouse, Hotel;
- Parking Garage, Hospital, Commercial Center;
- Supermarket, Shopping mall;
- Train, Bus station, airport,etc

TESTED DATA:

- · Technical Requirements Version: 4
- Classification: Premium
- Light Output: 3000lm-6250lm
- Wattage: 24w/36w (2x2) 24w/36w/42w/50w (2X4)
- Efficacy: >125 lm/W
- Power Factor: >.90
- CCT: 3500K, 4000K, 5000 K
- CRI: >80
- THD: <15 %
- Frequency: 50-60Hz
- Input Voltage: AC120-277V
- IP Rating: IP20
- Working Environment: –4°F-113°F
- Beam Angle: 120°
- Dimming Compatible: Yes
- · Mercury Content: No Hg
- · Lens: Polycarbonate

WARRANTY:

E2 warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. Please see our complete warranty terms located at www.e2lightingusa.com.



LED Slim (1.97") TROFFER Fixtures E2-TRS22/24 Series

Page: 2 of 2

Ordering Information:

Family	Size	Wattage	Controls	ССТ	Sensor option	Emergency battery back up
E2-TRS	22 = 2X2	24 = 24W 36 = 36W	D= 0-10V Dimmable	35K = 3500K	1 = Microwave sensor	EM = 90 mins Emergency batter back up
	24 = 2X4	24 = 24W 36 = 36W 42 = 42W 50 = 50W	Blank= Non- Dimmable	40K = 4000K 50K = 5000K	(Blank) = No sensor	(Blank) = No

Technical Requirements Version: 4

Date Qualified: 11/14/2016 Product ID: PWJNKEKB

Categorization

Main: Indoor Luminaires
General Application: Troffer
Primary Use: 2x4 Luminaires for Ambient
Lighting of Interior Commercial Spaces

Classification: Premium Is Parent Product: No DLC Family Code: HHHCAM Dimming Status: Dimmable Listing Status: Listed

Reported Data

Version History

Family Data

Light Output: 6500 lm Wattage: 50 W Efficacy: 130 lm/W Power Factor: 0.9 CCT: 5000 K CRI: 80

Total Harmonic Distortion: 15 %