



LED MAGNETIC TROFFER LINEAR STRIPS LIGHT KIT E2-RTST Series



PRODUCT DESCRIPTION:

E2 Lighting's LED Linear Strip Kit is an energy efficient replacement for existing T12, T5 and T8 strip fixtures and troffers. The kit is designed to distribute uniform lighting within an aluminum extrusion lighting fixture. UL and ETL classified/recognized, UL and ETL listed, DLC Premium listed and RoHs compliant.

FEATURES:

- High-power magnets and quick connect provide for easy installation
- Frosted, clear or no cover options available
- 50,000 Hours L70 Lifespan
- ETL and DLC® Premium 4

APPLICATION:

- Indoor Retrofit Kit
- Parking Garage, Warehouse, Offices, Restrooms, Storage Units and Stairwell Environments

TESTED DATA:

- Technical Requirements Version: 4
- Classification: Premium
- Light Output: 3120-10560 lm
- Wattage: 20, 24, 30, 40, 45, 60, 80 W
- Efficacy: >130 lm/W
- Power Factor: <0.99
- CCT: 4000-5000 K
- CRI: >80
- THD: <15 %
- Frequency: 50-60Hz
- Input Voltage: AC120-277V
- IP Rating: IP20
- Working Environment: -4°F-113°F
- Beam Angle: 120-160°
- Dimming Compatible: Yes
- Mercury Content: No Hg
- Lens: Polycarbonate

WARRANTY:

E2 warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. Please see our complete warranty terms located at www.e2lightingusa.com.

Model	Retrofit Type	Watts	Voltage	CCT	CRI	Lumens
E2-RTST124	(1) Strip; 2ft x 4ft troffers/4ft strip fixture	24W	AC100-277V	4000K-5000K	>80	3120-3216lm
E2-RTST230	(2) Strips; 2ft x 4ft troffers/4ft strip fixture	30W				4050-4170lm
E2-RTST240	(2) strips; 2ft x 4ft troffers/4ft strip fixture	40W				5200-5360lm
E2-RTST345	(3) Strips; 2ft x 4ft troffers/4ft strip fixture	45W				6075-6255lm
E2-RTST360	(3) Strips; 2ft x 4ft troffers/4ft strip fixture	60W				7800-8040lm
E2-RTST460	(4) Strips; 2ft x 4ft troffers/4ft strip fixture	60W				7800-8100lm
E2-RTST480	(4) Strips; 2ft x 4ft troffers/4ft strip fixture	80W				10160-10560lm
E2-RTST2120	(1) Strip; 2ft x 2ft troffers/2ft strip fixture	20W				2500-2700lm
E2-RTST2230	(2) Strips; 2ft x 2ft troffers/2ft strip fixture	30W				3750-4050lm
E2-RTST2340	(3) Strips; 2ft x 2ft troffers/2ft strip fixture	40W				5000-5400lm

MODEL SELECTION Typical order example: E2-RTST2230D-40K-F					
Family	Size		Controls	CCT	Cover
E2-RTST	124	4ft (1)-Strip 24W	Blank= Non-Dimmable D= 0-10V Dimmable	40K= 4000K 45K= 4500K 50K= 5000K	F= Frosted C= Clear N= No Cover
	230	4ft (2)-Strip 30W			
	240	4ft (2)-Strip 40W			
	345	4ft (3)-Strip 45W			
	360	4ft (3)-Strip 60W			
	480	4ft (3)-Strip 80W			
	460	4ft (4)-Strip 60W			
	480	4ft (4)-Strip 80W			
	2120	2ft (1)-Strip 20W			
	2230	2ft (2)-Strip 30W			
	2340	2ft (3)-Strip 40W			



Evaluated to the following: A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Light-Emitting Diode (LED) Retrofit Luminaire Conversion Kits (UL-1598C) and are identified as CLASSIFIED with the ETL Listed Mark..